



General:	Assembled by A&I Manufacturing, Inc. Environmentally safe.
Fabric:	Translucent or Room Darkening spun lace, non woven fabric. 100% Polyester.
Head Rail:	1 1/2" High x 1 3/4" Deep extruded aluminum, with PVC end caps. Depth with installation bracket is 2".
Bottom Rail:	1/2" High x 1 5/8" deep extruded aluminum with PVC end caps.
Cordless Modules:	Cordless modules are constructed with clear PVC body. Lift cord is wound inside the module. Steel spring provides tension to pull the shade up. A steel d-rod link all modules together inside the head rail.
Lift Cord:	Shall be braided polyester and of sufficient length to control the raising and lowering of the shade. Outside diameter is 0.9mm.
Weights:	100% Steel, Zinc plated with double sided tape.
Handle:	100% PVC
Installation Brackets:	Constructed of cold rolled steel. Zinc plated. Hex head screws are included. Intermediate brackets spaced no wider than 36" apart.
Sizes:	Outside mounted window coverings will be made to exact ordered measurements. Inside mounted horizontal shades will have 1/2" deducted at the factory from width. <i>See Product Limits.</i>

Product Limits

Controls (Manual)	Min. Width	Max. Width	Min. Drop	Max. Drop
Cordless	12"	84"	5"	*82"

Maximum Sq. Footage *48 Sq. Ft. Under Warranty

* Exceptions Available Upon Request

	WARNING		ADVERTENCIA
	Cords on window covering products present a potential strangulation hazard.		Las cuerdas y cadenas y persianas presentan un peligro de estrangulación.
	For child safety, consider cordless alternatives or products with inaccessible cords.		Para la seguridad de los niños, considere alternativas sin cuerdas o productos con cuerdas y cadenas inaccesibles.
<small>SAFLAB-3 04/2013</small>	<small>ANSI/WCMA 5.1.4</small>	<small>SAFLAB-3 04/2013</small>	<small>ANSI/WCMA 5.1.4</small>

