



1014 - Linen
1% Openness

Fabric Width	98" - 118"
Fabric Composition	30% Polyester, 70% PVC
Mesh/in	64 Warp-40 Fill
Weight	14.157 oz./yd. ² - 480 g/m ²
Fabric Thickness	± 0.026 mm
Openness Factor	1%
UV Blockage	Approximately 99%
Color Fastness	Class 4.5 (AATCC 16-2003)
Fire Resistance	NFPA701 (USA)
Environment	OEKO-TEX 100

Transmittance	Reflection	Absorption
09	50	41

Certifications



The Greenguard Environmental Institute is an industry-independent organization that aims to protect human health and improve quality of life by enhancing indoor air quality and reducing people's exposure to chemicals and other pollutants.



Oeko-Tex Standard 100 or Oeko-Tex Standard 100 is an independent testing and certification system for textile products from all stages of production along the textile value chain.



Fire Reaction Certificate
NFPA - 701-1999 (USA)

In the case of draperies, curtain, and similar hanging textiles, the standard that applies is NFPA 701: Standard methods of fire tests for flame propagation of textiles and films this test measures the flammability of a fabric when it is exposed to specific sources of ignition.

Fabric color pictured above can vary from printers.
Please see an actual sample piece for true color.